



**UNIVERSITI PUTRA MALAYSIA**

**MECHANICAL PROPERTIES OF FULL SIZE KAPUR  
(DRYOBALANOPS SPP.) BEAMS AND CORRELATION  
FOR DIFFERENT NDT METHODS**

**ALIK DUJU**

**FH 2002 14**

**MECHANICAL PROPERTIES OF FULL SIZE KAPUR  
(*DRYOBALANOPS* SPP.) BEAMS AND CORRELATION  
FOR DIFFERENT NDT METHODS**

**By**

**ALIK DUJU**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra  
Malaysia, in Fulfilment of the Requirement for the  
Degree of Master of Science**

**June 2002**



## DEDICATION

*Dedication to my wife Dumang Dullah, son Lawrence Insol  
and daughters Delphanie Lonnie and Valarie Ching for their  
time, concern and moral support during the period of my study.*

Abstract of thesis presented to the Senate of Universiti Putra Malaysia  
in fulfilment of the requirement for the degree of Master of Science

**MECHANICAL PROPERTIES OF FULL SIZE KAPUR  
(*DRYOBALANOPS* SPP.) BEAMS AND CORRELATION  
FOR DIFFERENT NDT METHODS**

**By**

**ALIK DUJU**

**June 2002**

**Chairman: Mohd Ariff Jamaludin, Ph.D.**

**Faculty: Forestry**

To cope with a large number of species and difficulties in species identification of tropical timbers, development of strength grading would be highly needed for an efficient and effective utilisation of structural components of our tropical timbers. To do that, an acceptable method of predicting timber strength has to be established in order to develop the confidence in using timbers as construction materials.

A total of 6 species of Kapur (*Dryobalanops* spp.) namely, Kapur bukit (*Dryobalanops beccarii* Dyer), Kapur empedu (*Dryobalanops fusca* V. Sl.), Kapur kelansau (*Dryobalanops oblongifolia* Dyer), Kapur paji (*Dryobalanops lanceolata* Burck), Kapur paya (*Dryobalanops rappa* Becc.) and Kapur peringgi (*Dryobalanops sumatrensis* (J. F. Gmelin) Kosterm) were used in this study. The trees selected for sampling possessed a healthy grown, straight bole and with

minimum diameter of 450 mm were collected from Mixed Dipterocarp Forest and Peat Swamp Forest. The sampling of test specimens was made throughout the whole lengths of tree bole. The nominal dimensions of 50 mm by 100 mm by 2000 mm and 50 mm by 100 mm by 3000 mm were used for bending and tensile tests both evaluated at green and air-dried conditions, respectively. The British Standard, BS 5820:1979 and BS 373:1957 were adopted to determine the strength of structural size and small clear specimens, respectively. The total number of samples tested were 240 pieces for bending and tensile tests at each test condition, respectively. In this study, six methods of measuring modulus of elasticity viz., longitudinal fundamental vibration frequency ( $E_{fr}$ ), ultrasonic wave propagation ( $E_{usw}$ ), deflection using dead weight loading at flatwise ( $E_{dwl}$ ), deflection using dead weight loading at edgewise ( $E_{dwe}$ ), apparent ( $E_{app}$ ) and true ( $E_{tru}$ ) were compared to predict the bending strength of full size structural components. Whilst for tensile strength, only three methods namely longitudinal fundamental vibration frequency ( $E_{fr}$ ), ultrasonic wave propagation ( $E_{usw}$ ) and modulus of elasticity in tension ( $E_{ts}$ ) were applied.

It was indicated that the average moisture content was 54.05% for green and 15.56% for air-dried condition. It took an average of 9 months to dry structural size samples from green to dry until it reached the equilibrium moisture content. Moisture content plays an important role in strength especially below fibre saturation point. It was found that the rate of change in bending strength and modulus of elasticity were 1.50% and 0.36% respectively for every percent changes of moisture below fibre saturation point. At the 5<sup>th</sup> percentile, it was

indicated that there was a difference both in bending and tensile strength in which moisture has significant effect on strength. Based on its density, Kapur bukit exhibited the heaviest followed by Kapur peringgi, Kapur paji, Kapur kelansau, Kapur empedu and Kapur paya respectively with their mean basic density of  $0.67 \text{ g/cm}^3$  and mean air-dried density of  $0.77 \text{ g/cm}^3$ . Hence, this species could be classified under Medium Hardwood:

Results of the study revealed that Kapur bukit was the strongest in term of bending strength followed by Kapur peringgi, Kapur paji, Kapur kelansau, Kapur empedu and lastly the weakest was Kapur paya, both at green and air-dried conditions. The overall average of bending strength was 68.14 MPa and 79.82 MPa at green and air-dried conditions, respectively. Whilst in term of tensile strength, Kapur bukit still indicated the highest strength followed by Kapur kelansau, Kapur paji, Kapur peringgi, Kapur empedu and Kapur paya both at green and air-dried conditions, respectively. The average tensile strength was 62.10 MPa and 71.50 MPa tested at both conditions, respectively. However, it was observed that there was a significant difference in bending strength and tensile strength between the timber species at 95% level of confidence. Further studies need to be carried out on regrouping the Kapur species according to their strength.

Results indicated weak correlation between visual parameters (i.e. knot size ratio at flatwise, knot size ratio at edgewise and sloping grain) with  $E_{fr}$ ,  $E_{usw}$ ,  $E_{dwf}$ ,  $E_{dwe}$ ,  $E_{app}$ ,  $E_{tru}$ ,  $E_{ts}$ , bending strength and tensile strength both at green and air-

dried conditions. Thus, it could be concluded that single visual parameter could not be used for predicting the strength properties of structural size timber. However, further study need to be carried out to incorporate all these visual parameters and others as specified under the Malaysian Grading Rules.

Strong correlation was observed between nondestructive moduli of elasticity both for dynamic and static. The same trend was also observed with bending and tensile strength tested at green and air-dried conditions. Hence, all the different nondestructive testing methods used in obtaining moduli of elasticity could be used to predict the strength properties of structural size timber. However, it is not recommended to use  $E_{usw}$  to predict the strength at green condition as the results indicated that high moisture content had a great influence on propagation time travel inside the timber. Thus, predicting the timber strength using  $E_{usw}$  was only advisable for air-dried timber samples. Linear regression equations were established to predict the strength of timber at both testing conditions. Among nondestructive methods,  $E_r$  seemed to be the best compared to  $E_{usw}$ ,  $E_{dwf}$ , and  $E_{dwe}$ . Fundamental vibration frequency method had the advantages, as it was more convenient and reliable, fast, easy to operate, easy to handle and most importantly of its non-contact measurement. Even though  $E_{app}$ ,  $E_{tru}$  and  $E_{ts}$  indicated a good correlation with strength, however, these methods were found to be rather slow and more laborious in obtaining the test results. Furthermore, the testing machines used were very expensive.

The strength values obtained from small defect-free specimens indicated a weak correlation in predicting the strength values of structural size timber. Timber properties of structural size samples were very much difference compared to that of small defect-free specimens as earlier ones contained a lot of wood defects and other inherent factors that affected the strength. Bending strength ratio is the best to express their relationship and it was found that the ratio of almost defect-free structural size and small clear specimens were 0.75 and 0.77 for green and air-dried conditions, respectively.

There was a weak correlation between pilodyn-pin penetration depth with bending and tensile strength, however a slightly a better correlation was observed with basic and air-dried density. There was a strong possibility that this method could be used to predict the density. Further study need to be carried out in the future to substantiate this correlation. The equipment used is reasonably cheap, simple and easy to handle and therefore tapping the usage to predict the density is worthwhile to consider. Various types of rupture pattern were also discussed.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia  
sebagai memenuhi keperluan untuk ijazah Master Sains.

**SIFAT-SIFAT MEKANIKAL KAYU BERSAIZ PENUH KAPUR  
(*DRYOBALANOPS* SPP.) DAN KORELASI UNTUK BERLAINAN  
KAEDAH PENILAIAN TANPA MUSNAH**

Oleh

**ALIK DUJU**

**Jun 2002**

**Pengerusi: Mohd Ariff Jamaludin, Ph.D.**

**Fakulti: Perhutanan**

Untuk menangani kepelbagaian spesis yang banyak dan masalah mengenalpasti spesis kayu tropika, pembangunan pemeringkatan kekuatan kayu sangatlah diperlukan supaya menggunakan komponen-komponen kayu bersaiz struktur dapat digunakan dengan lebih efektif dan efisien. Dengan itu, satu kaedah yang boleh diterima bagi meramalkan kekuatan kayu perlu diwujudkan bagi meyakinkan penggunaan kayu sebagai bahan binaan.

Sebanyak 6 spesis kayu Kapur (*Dryobalanops* spp.) terdiri daripada Kapur bukit (*Dryobalanop beccarii* Dyer), Kapur empedu (*Dryobalanops fusca* V. Sl.), Kapur kelansau (*Dryobalanops oblongifolia* Dyer), Kapur paji (*Dryobalanops lanceolata* Burck), Kapur paya (*Dryobalanops rappa* Becc.) dan Kapur peringgi (*Dryobalanops sumatrensis* (J. F. Gmelin) Kosterm) telah digunakan dalam kajian ini. Kayu yang dipilih mempunyai pertumbuhan yang baik, batang yang

lurus dan berdiameter minima 450 mm dipungut dari Hutan Dipterokarp Campuran dan Hutan Paya Gambut. Pensampelan spesimen ujian diambil dari seluruh batang kayu. Dimensi kayu yang berukuran 50 mm kali 100 mm kali 2000 mm dan 50 mm kali 100 mm kali 3000 mm digunakan untuk ujian kekuatan lenturan dan kekuatan tegangan yang dinilai dalam keadaan basah dan kering udara masing-masing. Piawaian British, BS 5820:1979 dan BS 373:1957 telah digunakan untuk menguji kekuatan sampel kayu bersaiz struktur dan bersaiz kecil masing-masing. Sejumlah 240 sampel kayu telah digunakan bagi ujian kekuatan lenturan dan kekuatan tegangan pada tiap-tiap keadaan ujian masing-masing. Dalam kajian ini, sebanyak enam kaedah bagi mengukur modulus kenyalan iaitu, frekuensi gegaran asas secara membujur ( $E_{fr}$ ), perambatan gelombang ultrasonik ( $E_{usw}$ ), pemesanan oleh beban mati merata ( $E_{dwr}$ ), pemesanan oleh beban mati secara sisi ( $E_{dws}$ ), modulus kenyalan ketara ( $E_{app}$ ) dan modulus kenyalan benar ( $E_{tru}$ ) telah dibandingkan bagi meramalkan kekuatan lenturan komponen kayu yang bersaiz struktur. Manakala untuk kekuatan tegangan, hanya tiga kaedah iaitu,  $E_{fr}$ ,  $E_{usw}$  dan modulus kenyalan dalam tegangan ( $E_{ts}$ ) telah dijalankan.

Adalah didapati bahawa purata kandungan lembapan sampel kayu yang telah diuji ialah 54.04% bagi keadaan basah dan 15.56% bagi keadaan kering udara. Masa yang diperlukan untuk mengeringkan sampel kayu dari keadaan basah sehingga sampel tersebut mencapai tahap kandungan lembapan yang seimbang ialah 9 bulan. Kandungan lembapan memainkan peranan yang penting dalam kekuatan kayu terutamanya dalam keadaan kandungan

lembapan kurang daripada takat tepu gentian. Didapati bahawa kadar perubahan kekuatan lenturan dan modulus kenyalan adalah 1.50% dan 0.36% masing-masing setiap peratus perubahan lembapan kurang daripada takat tepu gentian. Pada tahap peraturan kelima, didapati perbezaan yang ketara berlaku pada kedua-dua kekuatan lenturan dan kekuatan tegangan dalam keadaan basah dan kering udara. Berdasarkan ketumpatan kayu, Kapur bukit didapati paling berat diikuti Kapur peringgi, Kapur paji, Kapur kelansau, Kapur empedu dan Kapur paya masing-masing. Purata ketumpatan asas adalah  $0.67\text{g/cm}^3$  dan ketumpatan kering udara adalah  $0.77\text{ g/cm}^3$ . Oleh yang demikian, spesis ini boleh dikelaskan dalam kumpulan Kayu Keras Sederhana.

Kajian dapati bahawa Kapur bukit adalah paling kuat berdasarkan kekuatan lenturan diikuti oleh Kapur peringgi, Kapur paji, Kapur kelansau, Kapur empedu dan Kapur paya pada kedua-dua keadaan basah dan kering udara. Purata kekuatan lenturan adalah 68.14 MPa dan 79.82 MPa pada keadaan basah dan kering udara masing-masing. Manakala, berdasarkan kekuatan tegangan, Kapur bukit masih memberi kekuatan yang paling tinggi diikuti Kapur kelansau, Kapur paji, Kapur peringgi, Kapur empedu dan Kapur paya. Purata kekuatan tegangan adalah 62.10 MPa dan 71.50 MPa. Walau bagaimana, didapati perbezaan yang bererti pada kekuatan lenturan dan kekuatan tegangan dengan spesis kayu pada tahap 95%. Oleh yang demikian, kajian lanjutan harus dijalankan untuk membahagikan spesis Kapur kepada kumpulan-kumpulan tertentu berdasarkan kekuatan.

Keputusan menunjukkan hubung kait yang lemah diantara parameter yang menggunakan penglihatan (iaitu, nisbah saiz buku cara rata, nisbah saiz buku cara sisi dan ira serong) dengan  $E_{fr}$ ,  $E_{usw}$ ,  $E_{dwf}$ ,  $E_{dwe}$ ,  $E_{app}$ ,  $E_{tru}$ ,  $E_{ts}$ , kekuatan lenturan dan kekuatan tegangan yang telah dinilai pada keadaan basah dan kering udara masing-masing. Oleh yang demikian, boleh disimpulkan bahawa sesuatu parameter yang telah dinyatakan diatas tidak sesuai digunakan untuk meramalkan ciri-ciri kekuatan kayu yang bersaiz struktur. Walau bagaimanapun, kajian terperinci harus dijalankan dengan menggabungkan kesemua parameter dan lain-lain parameter seperti yang dinyatakan dalam Peraturan Pemeringkatan Malaysia.

Hubung kait yang kuat didapati diantara tanpa musnah modulus kenyalan sama ada secara dinamik ataupun statik. Keputusan menunjukkan trend yang sama diperolehi dengan kekuatan lenturan dan kekuatan tegangan dalam keadaan basah dan kering udara. Oleh yang demikian, kesemua keadah yang telah digunakan memperolehi modulus kenyalan boleh digunakan untuk meramalkan ciri-ciri kekuatan kayu yang bersaiz struktur. Tetapi, kaedah  $E_{usw}$  hanya baik untuk kayu yang berkeadaan kering udara. Pada kayu yang keadaan basah, lembapan yang tinggi mempengaruhi masa perambatan melalui kayu. Persamaan regresi linear telah diwujudkan bagi menanggarkan kekuatan lenturan dan kekuatan tegangan kayu dengan keadah tertentu dalam keadaan basah dan kering udara. Daripada kesemua keadah tanpa musnah,  $E_{fr}$  merupakan keadah yang baik sekali dibandingkan  $E_{usw}$ ,  $E_{dwf}$  dan  $E_{dwe}$ . Kaedah frekuensi asas gegaran mempunyai kebaikan dari segi boleh dipercayai, senang

digunakan, senang dikendalikan dan pengukuran tidak melalui sentuhan. Meskipun,  $E_{app}$ ,  $E_{tu}$  dan  $E_{ts}$  menunjukkan korelasi yang baik tetapi keadaan tersebut didapati memerlukan masa yang lama dan tenaga kerja yang banyak bagi memperolehi keputusan ujian. Tambahan, harga mesin penguji yang digunakan adalah terlampau mahal.

Keputusan menunjukkan korelasi diantara nilai kekuatan kayu yang didapati daripada sampel kayu yang bersaiz kecil dan kayu yang bersaiz struktur adalah kurang memuaskan. Didapati sifat-sifat kekuatan kayu agak berbeza diantara kedua-dua sampel tersebut. Ini adalah disebabkan kayu bersaiz struktur banyak mengandungi kecacatan kayu dan faktor-faktor dalaman yang boleh mempengaruhi kekuatan. Nisbah kekuatan lenturan merupakan nilai yang terbaik bagi menyatakan hubungan tersebut. Didapati bahawa nisbahnya adalah 0.75 dan 0.77 pada keadaan basah dan kering udara masing-masing.

Terdapat korelasi yang lemah diantara kedalaman pin pilodyn dengan kekuatan lenturan dan kekuatan tegangan, tetapi keputusan menunjukkan korelasi yang lebih baik didapati dengan asas ketumpatan dan ketumpatan kering udara. Ini menunjukkan kemungkinan besar bahawa keadaan ini mempunyai potensi yang baik dalam meramalkan ketumpatan kayu. Oleh yang demikian, kajian lanjutan harus dijalankan pada masa hadapan bagi mengesahkan korelasi tersebut. Disebabkan peralatan ini agak murah, mudah dan senang digunakan adalah wajar diambil perhatian selanjutnya. Jenis-jenis kecacatan selepas ujian pada sampel juga dibincangkan.

## **ACKNOWLEDGEMENTS**

The author wishes to express his sincere gratitude and appreciation to his supervisors' Dr. Mohd. Ariff Jamaludin, Associate Professor Dr. Mohd. Hamami Sahri and Dr. Paridah Md Tahir for their invaluable guidance, suggestions and constructive criticisms that lead to the completion of the research project.

Sincere thanks are due to the State Secretary of Sarawak Datuk Amar Haji Abdul Aziz Haji Husain for giving me the approval to pursue this master program for the duration of 2 years, Director of Forests Mr. Cheong Ek Choon and Senior Assistant Director of Forests (Utilization) Mr. Ling Wang Choon of Forest Department Sarawak for giving me the opportunity to use all the research equipment and testing facilities.

Acknowledgements are due to the Chairman of Sarawak Timber Association (STA) Dato Lau Hui Kang, General Manager Mr. Barney Chan, Technical and Research Manager Dr. Peter Kho and STA members for their generosity in awarding the research/education grants and any assistance one way or another.

The author likes to acknowledge the staff of Mechanical Testing Section of Timber Research and Technical Training Centre (TRTTC) particularly Assistant Research Officer Andrew Nyorik Nibu, Laboratory Assistant Nungah Liang, Junior Research Assistants Robert Sepek Minggit, Badihi Junaidi and Yeo Hui Choo, Laboratory/Plant Attendants Di Hail, Wilfred Sareng, Hasbullah Eli, Hasbi Bujang and Kumong Kaleng for assisting in the collection, preparation and testing of timber samples.

Finally, the author likes to convey his very special gratitude to his mother, brother, sisters, friends and colleagues for their encouragement, concern and moral support throughout the course of his study.

I certify that an Examination Committee met on 3<sup>rd</sup> June 2002 to conduct the final examination of Alik Duju on his Master of Science thesis entitled "Mechanical Properties of Full Size Kapur (*Dyobalanops* spp.) Beams and Correlation for Different NDT Methods" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

**Barkawi Sahari, Ph.D.,**  
Associate Professor,  
Faculty of Engineering,  
Universiti Putra Malaysia.  
(Chairman)

**Mohd Ariff Jamaludin, Ph.D.,**  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Member)

**Mohd. Hamami Sahri, Ph.D.,**  
Associate Professor,  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Member)

**Paridah Md. Tahir, Ph.D.,**  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Member)



---

**AINI IDERIS, Ph.D.,**  
Professor/Dean  
School Graduate Studies,  
Universiti Putra Malaysia.

Date: 26 OCT 2002



This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

**Mohd Ariff Jamaludin, Ph.D.,**  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Chairman)

**Mohd. Hamami Sahri, Ph.D.,**  
Associate Professor,  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Member)

**Paridah Md. Tahir, Ph.D.,**  
Faculty of Forestry,  
Universiti Putra Malaysia.  
(Member)

---

**AINI IDERIS, Ph.D.,**  
Professor/Dean  
School of Graduate Studies,  
Universiti Putra Malaysia.

Date:

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



---

ALIK DUJU

Date: 3 July 2002

## TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	viii
ACKNOWLEDGEMENTS	xiii
APPROVAL SHEETS	xv
DECLARATION FORM	xvii
LIST OF TABLES	xxi
LIST OF FIGURES	xxii
LIST OF ABBREVIATIONS	xxvii
 <b>CHAPTER</b>	
 1 INTRODUCTION	 1
1.1 Background	1
 2 LITERATURE REVIEW	 5
2.1 Forestry of Sarawak	5
2.2 Forest industry sector of Sarawak	6
2.3 Utilisation of timber species in construction	8
2.4 Kapur species ( <i>Dryobalanops</i> spp.)	9
2.5 Grading method in Malaysia	11
2.6 Visual grading of timber	12
2.7 Mechanical grading of timber	14
2.8 Nondestructive evaluation of timber	15
2.8.1 Frequency vibration method	18
2.8.2 Ultrasonic method	19
2.8.3 Bending deflection method	20
2.8.4 Penetration depth of pin method	21
2.9 Factors affecting strength properties	22
2.9.1 Timber species	23
2.9.2 Density	24
2.9.3 Moisture content	25
2.9.4 Defects	26
2.9.4.1 Knots	26
2.9.4.2 Sloping grain	27
2.9.4.3 Other factors	28



<b>3</b>	<b>METHODOLOGY</b>	<b>29</b>
3.1	Materials	29
3.2	Test methods	33
3.2.1	Nondestructive testing	33
3.2.1.1	Measurement of modulus of elasticity by longitudinal vibration frequency method	34
3.2.1.2	Measurement of modulus of elasticity by propagation ultrasonic wave method	35
3.2.1.3	Measurement of modulus of elasticity by dead weight loading bending deflection method	36
3.2.2	Destructive testing	37
3.2.2.1	Static bending test of structural size specimen	37
3.2.2.2	Static bending of small clear specimen	40
3.2.2.3	Tensile test of structural size specimen	41
3.2.2.4	Measurement of penetration depth of pin	42
3.2.3	Physical properties	43
3.2.3.1	Moisture content determination	43
3.2.3.2	Density determination	44
3.2.3.3	Slope of grain (Grain angle)	45
3.2.3.4	Knot ratio	46
3.2.4	Statistical analysis	46
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>47</b>
4.1	Main test results of Kapur species	47
4.1.1	Nondestructive moduli of elasticity of structural timber	48
4.1.2	Bending strength of structural timber	50
4.1.3	Density of structural timber	51
4.1.4	Moisture content of structural timber	52
4.1.5	Bending strength of small clear specimen	53
4.2	Moduli of elasticity and tensile strength of structural timber	57
4.3	Relationships between visual parameters and strength properties	60
4.4	Relationships between moduli of elasticity by nondestructive and moduli of elasticity in bending	63
4.5	Relationships between moduli of elasticity and modulus of rupture	66
4.6	Relationships between visual parameters and tensile strength	75
4.7	Relationships between nondestructive moduli of elasticity and modulus of elasticity in tension	78

4.8	Relationships between moduli of elasticity and tensile strength	82
4.9	Effect of density on bending strength	86
4.10	Effect of density on tensile strength	91
4.11	Effect of moisture content on strength properties	94
4.12	Relationships between pilodyn pin penetration with density, bending and tensile strength	97
4.13	Relationships between small clear specimens and structural size specimens in bending strength	101
4.14	Rupture types of bending samples	104
5	CONCLUSION	109
	REFERENCES	114
	APPENDICES	124
	BIODATA OF AUTHOR	159

## LIST OF TABLES

	<b>Page</b>
Table 1 : Number and types of timber mills in Sarawak	7
Table 2 : Nondestructive tests methodologies for wood products in North America	16
Table 3 : Common and botanical names of Kapur species and their locality	33
Table 4 : Main results on bending strength of Kapur species	56
Table 5 : Main results on tensile strength of Kapur species	59
Table 6 : Correlation of coefficient between visual parameters and bending strength of Kapur species at green condition	61
Table 7 : Correlation of coefficient between visual parameters and bending strength of Kapur species at air-dried condition	62
Table 8 : Correlation of coefficient between modulus of elasticity from nondestructive tests and modulus of elasticity from destructive bending tests of Kapur species at green condition	64
Table 9 : Correlation of coefficient between modulus of elasticity from nondestructive tests and modulus of elasticity from destructive bending tests of Kapur species at air-dried condition	64
Table 10 : Correlation of coefficient between visual parameters and tensile strength of Kapur species at green condition	77
Table 11 : Correlation of coefficient between visual parameters and tensile strength of Kapur species at air-dried condition	77

## LIST OF FIGURES

	<b>Page</b>
Figure 1 : Kapur empedu tree selected for sampling	30
Figure 2 : Localities of Kapur species collected	32
Figure 3 : Test set-up for longitudinal vibration frequency method	34
Figure 4 : Test set-up for stress wave propagation time measuring method	36
Figure 5 : Test set-up for dead weight loading method	37
Figure 6 : Test set-up for static bending test	38
Figure 7 : 250 kN Minebea universal testing machine	39
Figure 8 : Static bending set-up on the 50 kN Instron universal testing machine	40
Figure 9 : Test set-up for tensile strength parallel to grain	41
Figure 10 : Tensile test set-up on the 1000 kN Maekawa horizontal tensile machine	42
Figure 11 : Pilodyn wood tester	43
Figure 12 : Swivel handle scribe for determination of slope of grain	45
Figure 13 : Relationship between modulus of elasticity ( $E_r$ ) and modulus of rupture of structural timber at green condition	69
Figure 14 : Relationship between modulus of elasticity ( $E_{usw}$ ) and modulus of rupture of structural timber at green condition	70
Figure 15 : Relationship between modulus of elasticity ( $E_{dwt}$ ) and modulus of rupture of structural timber at green condition	70

Figure 16	: Relationship between modulus of elasticity ( $E_{dwe}$ ) and modulus of rupture of structural timber at green condition	71
Figure 17	: Relationship between modulus of elasticity ( $E_{app}$ ) and modulus of rupture of structural timber at green condition	71
Figure 18	: Relationship between modulus of elasticity ( $E_{tu}$ ) and modulus of rupture of structural timber at green condition	72
Figure 19	: Relationship between modulus of elasticity ( $E_{fr}$ ) and modulus of rupture of structural timber at air-dried condition	72
Figure 20	: Relationship between modulus of elasticity ( $E_{usw}$ ) and modulus of rupture of structural timber at air-dried condition	73
Figure 21	: Relationship between modulus of elasticity ( $E_{dwt}$ ) and modulus of rupture of structural timber at air-dried condition	73
Figure 22	: Relationship between modulus of elasticity ( $E_{dwe}$ ) and modulus of rupture of structural timber at air-dried condition	74
Figure 23	: Relationship between modulus of elasticity ( $E_{app}$ ) and modulus of rupture of structural timber at air-dried condition	74
Figure 24	: Relationship between modulus of elasticity ( $E_{tu}$ ) and modulus of rupture of structural timber at air-dried condition	75
Figure 25	: Relationship between modulus of elasticity ( $E_{fr}$ ) and modulus of elasticity in tension ( $E_{ts}$ ) of structural timber at green condition	79
Figure 26	: Relationship between modulus of elasticity ( $E_{usw}$ ) and modulus of elasticity in tension ( $E_{ts}$ ) of structural timber at green condition	79



Figure 27	: Relationship between modulus of elasticity ( $E_{fr}$ ) and modulus of elasticity ( $E_{usw}$ ) of structural timber at green condition	80
Figure 28	: Relationship between modulus of elasticity ( $E_{fr}$ ) and modulus of elasticity in tension ( $E_{ts}$ ) of structural timber at air-dried condition	80
Figure 29	: Relationship between modulus of elasticity ( $E_{usw}$ ) and in tension ( $E_{ts}$ ) of structural timber at air-dried condition	81
Figure 30	: Relationship between modulus of elasticity ( $E_{fr}$ ) and modulus of elasticity ( $E_{usw}$ ) of structural timber at air-dried condition	81
Figure 31	: Relationship between modulus of elasticity ( $E_{fr}$ ) and tensile strength of structural timber at green condition	83
Figure 32	: Relationship between modulus of elasticity ( $E_{usw}$ ) and tensile strength of structural timber at green condition	84
Figure 33	: Relationship between modulus of elasticity in tension ( $E_{ts}$ ) and tensile strength of structural timber at green condition	84
Figure 34	: Relationship between modulus of elasticity ( $E_{fr}$ ) and tensile strength of structural timber at air-dried condition	85
Figure 35	: Relationship between modulus of elasticity ( $E_{usw}$ ) and tensile strength of structural timber at air-dried condition	85
Figure 36	: Relationship between modulus of elasticity in tension ( $E_{ts}$ ) and tensile strength of structural timber at air-dried condition	86
Figure 37	: Relationship between basic density and modulus of elasticity ( $E_{app}$ ) of structural timber	88
Figure 38	: Relationship between basic density and modulus of elasticity ( $E_{tu}$ ) of structural timber	88
Figure 39	: Relationship between basic density and modulus of rupture of structural timber	89